



Wide-view mast design and downward-moving cab instrument panel increase the driver's operating field of vision by 30% and improve safety



LED lamps, energy saving, long life, high brightness.



USA Cascade slider, lifetime warranty.



All models are equipped with Toyota intelligent comfort seats and enlarged and thickened engine hood as standard



Independently developed and produced integral casting counterweight, which is more than at least 100KG heavier than other competitors, maintaining value and more stable



Standard high-power AC motor, strong power



PARAMETERS & PERFORMANCE CPD25S

General

Manufacturer		SHANGCHA
Model		CPD25S
Power Type		Lithium battery
Rated Load Capacity	Q(kg)	2500
Load Centre	C(mm)	500

Characteristic & Dimension

Rated Lift Height	H3(mm)	3000
Free Lift Height	H2(mm)	145
Mast Tilt Angle (F/R, α°/β°)	$^\circ$	6°/10
Travel Speed (Full Load/No Load)	km/h	12/14
Lifting Speed (Full Load/No Load)	mm/s	280/400
Max.Gradeability(No Load/Full Load)	%	20/15
Turning Radius	Wa(mm)	2390
Total weight	kg	3800
Wheelbase	Y(mm)	1660
Fork Size (LxWxT)	mm	1070×120×45
Fork Overhang	X1(mm)	475
Rear Overhang	X2(mm)	510
Length to Face of Fork (Without Fork)	L1(mm)	2645
Overall Width	B1(mm)	1174
Mast Lowered Height	H1(mm)	2060
Overhead Guard Height	H5(mm)	2170

Power & Transmission

Battery	V/Ah	80/280
Drive Motor	kw	10
Lift Motor	kw	12
Operating Pressure (For Attachments)	Mpa	17.5
Controller		SANTROLL

Chassis

Tyre (Front x 2)	B2(mm)	7.00-12-12PR
Tyre (Rear x 2)	B3(mm)	6.00-9-10PR

